



GROWING TOGETHER



**MULTIUSE
TIRES**

MULTIUSE TIRES



MULTIMAX MP 513 (R-1)



MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance applications. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds. Its reinforced bead ensures a longer service life and extra mileage to enhance productivity.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (Index)	Version
		Rec.	Alt.						
17"									
425/55 R 17	134 G	13	13.00	421	900	399	2645	-	STD
18"									
365/70 R 18	133 G	11	11 SDC; 12; 12 SDC	360	969	448	2933	-	STD
20"									
375/70 R 20	136 G	12	W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC	377	1034	472	3121	-	STD
405/70 R 20	136 G	13	13 SDC; 12 SDC	407	1076	493	3253	-	STD
425/75 R 20	148 G	13	13 SDC; 11 SDC; 12 SDC; 11; 12	421	1146	521	3479	-	STD
24"									
495/70 R 24	155 G	W 16 L	DW 15 L; DW 16 L; W 15 L	499	1304	588	3974	-	STD

STD: Standard





MULTIMAX MP 522



MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (Index)	Version
		Rec. 	Alt. 						
18"									
280/80 R 18	132 A8/B	9; 9 SDC	-	282	907	421	2727	350	STD
340/80 R 18 (12.5/80 R 18)	143 A8/B	11; 11 SDC; W 11	W 10; 12; 12 SDC	343	1001	458	3002	475	STD
20"									
340/80 R 20	144 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	343	1052	481	3212	500	STD
380/75 R 20 (14.5 R 20)	148 A8/B	W 12	W 11; 11; 12	384	1074	483	3251	500	STD
400/70 R 20 (16.0/70 R 20)	149 A8/B	13	12 SDC; 13 SDC; 14	404	1068	476	3199	525	STD
24"									
400/70 R 24	152 A8/B	13	DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L	404	1170	533	3527	575	STD
400/80 R 24	162 A8/B	DW 13	DW 12; DW 13 L; DW 14 L	404	1250	553	3778	600	STD
440/80 R 24	161 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1314	586	3956	625	STD
460/70 R 24 (17.5L R 24)	159 A8/B	DW 15 L	DW 14 L; DW 16 L	465	1250	568	3766	600	STD
500/70 R 24 (19.5L R 24)	164 A8/B	DW 16 L	DW 15 L; DW 18 L	503	1310	595	3890	625	STD
540/70 R 24	168 A8/B	DW 16 L	DW 18 L	530	1366	611	4133	650	STD
26"									
480/80 R 26	160 A8/B	DW 15 L	DW 16 L	479	1428	638	4287	675	STD
28"									
440/80 R 28	156 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1415	643	4278	675	STD

STD: Standard

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

MULTIUSE TIRES



MULTIMAX MP 527



TRACTION



STABILITY



HIGH PUNCTURE
RESISTANCE



CUT & CHIP
RESISTANCE



DURABILITY

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers in industrial applications. The tire shows an aggressive tread design providing excellent traction under any service condition. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (Index)	Version
		Rec.	Alt.						
18" 340/80 R 18	143 A8/B	11; 11 SDC; W 11	W 10; 12; 12 SDC	343	1001	455	2944	475	STD
20" 340/80 R 20	144 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	343	1052	-	-	500	STD
20" 400/70 R 20 (16.0/70 R 20)	149 A8/B	13	12 SDC; 13 SDC; 14	404	1068	494	3282	525	STD
24" 400/70 R 24	152 A8/B	13	DW 12; DW 13; DW 13 L; 13 SDC; DW 14 L	404	1170	-	-	575	STD
24" 400/80 R 24	162 A8/B	DW 13	DW 12; DW 13 L; DW 14 L	404	1250	578	3834	600	STD
24" 440/80 R 24	161 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1314	601	3985	625	STD
24" 460/70 R 24 (17.5L R 24)	159 A8/B	DW 15 L	DW 14 L; DW 16 L	465	1254	574	3801	600	STD
24" 500/70 R 24	164 A8/B	DW 16 L	DW 15 L; DW 18 L	503	1310	597	4019	625	STD
28" 440/80 R 28	156 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1415	648	4270	675	STD

STD: Standard





MULTIMAX MP 540



MULTIMAX MP 540 has been designed by BKT for multi-purpose vehicles in municipality/maintenance applications. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 540 allows to carry heavy loads at high speeds.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (Index)	Version
		Rec.	Alt.						
20" 335/80 R 20	149 K	11	-	340	1044	492	3258	-	STD

STD: Standard



RT 747 AGRO INDUSTRIAL



RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for backhoe loaders, compact loaders and telehandlers. Its extra wide lugs provide excellent grip and great stability in lift operations. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (Index)	Version
		Rec.	Alt.						
24" 460/70 R 24 (17.5L R 24)	152 A8/149 B	DW 15 L	DW 14 L; DW 16 L	465	1254	556	3840	575	STD
500/70 R 24 (19.5L R 24)	157 A8/154 B	DW 16 L	DW 15 L; DW 18 L	485	1320	585	3949	625	STD

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

MULTIUSE TIRES



CON STAR



HIGH LOAD
CAPACITY



DURABILITY



STABILITY



CUT & CHIP
RESISTANCE



CUT RESISTANT

CON STAR is particularly suitable for backhoe loaders, compact loaders and telehandlers in digging and loading applications. It features high load capacity along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
18"										
340/80 - 18 (12.5/80 - 18)	11	12; 11 SDC; 12 SDC; W 10; W 11	350	1015	460	3075	IND	-	TL	143 A8
20"										
340/80 - 20 (12.5/80 - 20)	11	12; 11 SDC; 12 SDC; W 10; W 11	350	1065	491	3272	IND	-	TL	144 A8
380/75 - 20 (14.5 - 20)	W 12	W 11; 12 SDC; 12; W 13; 13 SDC; 13	385	1080	500	3273	IND	-	TL	148 A8
400/70 - 20 (16.0/70 - 20)	13	12 SDC; 13 SDC; 14	405	1080	501	3303	IND	-	TL	156 A8
400/70 - 20 (16.0/70 - 20)	13	12 SDC; 13 SDC; 14	405	1080	501	3303	IND	16	TL	149 A8
24"										
400/70 - 24 (16.0/70 - 24)	13	DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L	395	1175	-	-	IND	-	TL	158 A8
400/80 - 24 (15.5/80 - 24)	DW 13	DW 1; DW 13 L; DW 14 L	405	1250	570	3781	IND	20	TL	162 A8
440/80 - 24 (17.0/80 - 24)	DW 14 L	DW 13; DW 13 L; DW 15 L	455	1315	610	3986	IND	22	TL	168 A8
460/70 - 24 (17.5L - 24)	DW 15 L	DW 14 L; DW 16 L	460	1250	-	-	IND	-	TL	159 A8
500/70 - 24 (19.5L - 24)	DW 16 L	DW 15 L; DW 18 L	505	1300	579	3926	IND	-	TL	164 A8
26"										
480/80 - 26 (18.4 - 26)	DW 15 L	DW 16 L	490	1410	643	4272	IND	-	TL	160 A8
28"										
440/80 - 28 (16.9 - 28)	DW 14 L	DW 13; DW 13 L; DW 15 L	450	1420	632	4299	IND	-	TL	156 A8

IND: Industrial



AT 603



AT 603 is a bias agro-industrial tire for backhoe loaders, compact loaders and compact dumpers in digging and loading applications. AT 603 has been engineered to ensure great traction on drive wheels providing the best performance on and off the road. The AT 603 “special” version offers improved cut and chip resistance while the “HD” version is ideal for heavy-duty service.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.										
18"												
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	STD	10	TL	-	131 A8	119 A8
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	HD	10	TL	-	131 A8	119 A8
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	SPL	10	TL	-	131 A8	119 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	12	TL	-	142 A8	129 A8
12.5/80 - 18	W 9	11	308	987	438	2892	SPL	12	TL	-	142 A8	129 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	16	TL	-	148 A8	135 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	18	TL	-	150 A8	138 A8

HD: Heavy Duty
SPL: Special
STD: Standard

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

MULTIUSE TIRES



AT 621 (R-4)



AT 621 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. The AT 621 tire features an extra deep tread which ensures great cut resistance and higher durability. AT 621 is available in several versions to meet the most differing user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.										
15" 33 X 12.5 - 15	10.00 F SDC	-	318	851	385	2493	STD	8	TT	-	-	-
16" 9.00 - 16	6.50 H	6.00 G	260	925	-	-	IND	16	TT	137 A6	-	-
12.5/70 - 16	10 LB	-	315	855	385	2584	STD	8	TL	-	-	-
18" 12.5/80 - 18	W 9	11.0	308	987	438	2892	STD	12	TT	-	142 A8	129 A8
12.5/80 - 18	W 9	11.0	308	987	438	2892	STD	12	TL	-	142 A8	129 A8
12.5/80 - 18	W 9	11	308	987	438	2892	SPL	12	TL	-	142 A8	129 A8
12.5/80 - 18	W 9	11.0	308	987	438	2892	STD	16	TT	-	148 A8	135 A8
12.5/80 - 18	W 9	11.0	308	987	465	2928	IND HD	16	TL	-	148 A8	135 A8
15.5/60 - 18	W 13	-	400	950	428	2871	STD	10	TL	-	-	-
15.5/70 - 18 (400/70 - 18)	W 13	-	400	1030	474	3111	STD	10	TL	-	-	-

STD: Standard
IND: Industrial
SPL: Special



AT 621 (R-4)



AT 621 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. The AT 621 tire features an extra deep tread which ensures great cut resistance and higher durability. AT 621 is available in several versions to meet the most differing user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.										
20"												
17.5/65 - 20	W 14 L	-	450	1090	490	3294	STD	10	TL	-	-	-
42 X 17 - 20	14.00 TG SDC	-	432	1073	480	3198	STD	10	TT	-	-	-
400/70 - 20	13	12 SDC; 13 SDC; 14	405	1090	-	-	STD	-	TL	149 A8	-	-
24"												
16.9 - 24	DW 15 L	DW 14 L	450	1302	582	3776	IND	12	TL	149 A8	-	-
17.5L - 24	DW 15 L	DW 14 L	450	1255	563	3640	STD	8	TL	139 A8	-	-
19.5L - 24	DW 16 L	-	482	1305	587	3936	STD	12	TL	151 A8	-	-
26"												
18.4 - 26	DW 16 L	DW 15 L	480	1425	636	4133	STD	12	TL	156 A8	-	-
28"												
16.9 - 28	DW 15 L	DW 14 L	450	1410	645	4247	IND	12	TT	152 A8	-	-
16.9 - 28	DW 15 L	DW 14 L	450	1410	645	4247	IND	12	TL	152 A8	-	-
30"												
16.9 - 30	DW 15 L	DW 14 L	450	1460	670	4398	IND	12	TL	153 A8	-	-

STD: Standard
IND: Industrial

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

MULTIUSE TIRES



MP 567



MP 567 is an agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15"										
11.5/80 - 15	8 LB	-	290	875	-	-	STD	12	TL	-
15.3"										
10.0/75 - 15.3	9.0	-	258	774	355	2310	STD	10	TL	-
10.0/75 - 15.3	9.0	-	258	774	355	2310	STD	12	TL	-
10.0/75 - 15.3	9.0	-	258	774	355	2310	STD	14	TL	-
10.0/75 - 15.3	9.0	-	258	774	355	2310	STD	18	TL	-
11.5/80 - 15.3	9.0	-	292	868	393	2578	STD	10	TL	-
11.5/80 - 15.3	9.0	-	292	868	393	2578	STD	14	TL	-
11.5/80 - 15.3	9.0	-	292	868	393	2578	STD	18	TL	-
18"										
10.5 - 18	9	9 SDC	270	905	415	2700	STD	10	TT	-
10.5 - 18	9	9 SDC	270	905	415	2700	STD	10	TL	-
10.5 - 18	9	9 SDC	270	905	415	2700	STD	12	TL	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	10	TT	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	10	TL	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	12	TT	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	12	TL	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	16	TL	-
12.5 - 18	11	12 SDC	325	990	450	2940	STD	16	TL	-

STD: Standard



MP 567



MP 567 is an agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
19.5"										
18 - 19.5	14.00	-	460	1104	498	3280	STD	14	TL	-
18 - 19.5	14.00	-	460	1104	498	3280	STD	16	TL	-
18 - 19.5	14.00	-	460	1104	498	3280	STD	18	TL	-
20"										
10.5 - 20	9	9 SDC	270	955	445	2880	STD	10	TT	-
10.5 - 20	9	9 SDC	270	955	445	2880	STD	10	TL	-
12.5 - 20	11.0	12 SDC	325	1040	475	3090	STD	10	TT	-
12.5 - 20	11.0	12 SDC	325	1040	475	3090	STD	10	TL	-
12.5 - 20	11.0	12 SDC	325	1040	475	3090	STD	12	TT	-
12.5 - 20	11.0	12 SDC	325	1040	475	3090	STD	12	TL	-
14.5 - 20	11	12 SDC	360	1116	495	3315	STD	10	TL	-
14.5 - 20	11	12 SDC	360	1116	495	3315	STD	12	TL	-
14.5 - 20	11	12 SDC	360	1116	495	3315	STD	14	TL	-
14.5 - 20	11	12 SDC	360	1116	495	3315	STD	16	TL	-
14.5 - 20	11	12 SDC	360	1116	495	3315	STD	18	TL	-
16.0/70 - 20 (405/70 - 20)	13 SDC	12	405	1128	490	3350	STD	14	TL	-
16.0/70 - 20 (405/70 - 20)	13 SDC	12	405	1128	490	3350	STD	14	TT	-

STD: Standard

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

MULTIUSE TIRES



MP 570



MP 570 is a road-oriented and agro-industrial tire, which is suitable for excavators and compact loaders. This tire provides good traction as well as excellent self-cleaning properties in all operating conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
18"										
12.5 - 18	11	12 SDC	308	990	450	2950	STD	10	TL	-
12.5 - 18	11	12 SDC	308	990	450	2950	STD	12	TL	-
20"										
12.5 - 20	11	12 SDC	335	1050	480	3130	STD	10	TL	-
12.5 - 20	11	12 SDC	325	1040	475	3090	STD	12	TL	-
14.5 - 20	11	12 SDC	360	1116	505	3325	STD	12	TL	-

STD: Standard



MP 585



MP 585 is a road-oriented and agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a tread pattern that offers maximum stability in the most difficult working conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
20"										
6.50 - 20	5.50 F	4.00 E; 5.00 F	200	875	-	-	STD	10	TT	-
10.5 - 20	9	9 SDC	273	970	455	2890	STD	10	TL	-
12.5 - 20	11	12 SDC	335	1050	480	3130	STD	12	TL	-

STD: Standard

MULTIUSE TIRES



MP 590



MP 590 is an agro-industrial tire suitable for loading operations with compact loaders, telehandlers and forklifts. This tire provides good traction and excellent stability as well as high load capacity to enhance productivity.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
22.5" 18 - 22.5 (445/65 - 22.5)	14.0	-	465	1190	530	3534	STD	16	TL	-
18 - 22.5 (445/65 - 22.5)	14.0	-	480	1190	530	3534	STD	20	TL	-

STD: Standard





MP 600



MP 600 is a road-oriented and agro-industrial tire, suitable for loading operations with compact loaders and telehandlers. This tire provides good traction and excellent stability along with an extended product life-cycle.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
18"										
10.5 - 18	9	9 SDC	272	920	420	2740	STD	10	TL	-
12.5 - 18	11	12 SDC	308	990	450	2950	STD	10	TL	-
12.5 - 18	11	12 SDC	308	990	450	2950	STD	12	TL	-
20"										
400/70 - 20 (16.0/70 - 20)	13 SDC	12	405	1085	-	-	STD	14	TL	-
24"										
400/70 - 24 (16.0/70 - 24)	13 SDC	12	405	1185	545	3530	STD	10	TL	-
400/70 - 24 (16.0/70 - 24)	13 SDC	12	405	1185	545	3530	STD	14	TL	-
400/70 - 24 (16.0/70 - 24)	13 SDC	12	405	1185	545	3530	SPL	14	TL	-
400/70 - 24 (16.0/70 - 24)	33.5	12	405	1185	545	3530	STD	18	TL	-

STD: Standard
SPL: Special

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

MULTIUSE TIRES



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific enduser requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
15.3" 10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	8	TT	119 A8	106 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	8	TL	119 A8	106 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	IND	8	TL	119 A8	106 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	10	TL	123 A8	111 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	14	TL	130 A8	118 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	18	TT	135 A8	122 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	18	TL	135 A8	122 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	8	TT	126 A8	114 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	8	TL	126 A8	114 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	10	TL	131 A8	119 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	12	TT	135 A8	123 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	12	TL	135 A8	123 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	14	TT	139 A8	126 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	14	TL	139 A8	126 A8
27 X 10 - 15.3	9.00	-	260	695	317	2071	STD	8	TT	107 A8	95 A8
27 X 10 - 15.3	9.00	-	260	695	317	2071	STD	8	TL	107 A8	95 A8

STD: Standard
IND: Industrial



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific enduser requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
16"											
6.00 - 16	4.00 E	4.50 E; 4½ K	164	735	343	2190	STD	6	TT	95 A8	83 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	6	TT	104 A8	92 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	8	TT	112 A8	99 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	8	TL	112 A8	99 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	HD	8	TT	112 A8	99 A8
9.0/70 - 16	W 7	-	222	760	355	2285	STD	10	TL	119 A8	106 A8
270/75 - 16 (10.0/75 - 16)	9.00	-	250	810	-	-	STD	-	TL	123 A8	111 A8
17"											
15.0/55 - 17	13.00	13	380	890	395	2608	STD	10	TL	134 A8	122 A8
15.0/55 - 17	13.00	13	380	890	395	2608	STD	14	TL	141 A8	129 A8
19.0/45 - 17	16.00	-	465	865	389	2578	STD	14	TL	144 A8	131 A8
420/55 - 17	13.00	-	430	910	407	2712	STD	14	TL	142 A8	129 A8
420/55 - 17	13.00	-	430	910	407	2712	STD	16	TL	145 A8	133 A8

STD: Standard
HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

MULTIUSE TIRES



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific enduser requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
18"											
7.50 - 18	5.50 F	4.50 E; 6.00 F; 5.00 F	209	854	407	2649	STD	6	TT	106 A8	94 A8
7.50 - 18	5.50 F	4.50 E; 6.00 F; 5.00 F	209	854	407	2649	STD	8	TT	114 A8	101 A8
10.5/80 - 18	W 9	9; W 8	274	907	405	2657	STD	10	TL	131 A8	119 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	12	TL	142 A8	129 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	SPL	12	TL	142 A8	129 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	16	TL	148 A8	135 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	18	TL	150 A8	138 A8
20"											
7.50 - 20	5.50 F	4.50 E; 6.00 F; 5.00 F	209	904	422	2695	STD	8	TT	116 A8	103 A8
16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	10	TL	147 A8	135 A8
16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	12	TL	151 A8	139 A8
16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	14	TL	154 A8	142 A8
16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	16	TL	156 A8	144 A8
400/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	IND	-	TL	-	-

STD: Standard
SPL: Special
IND: Industrial



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific enduser requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
24"											
15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	10	TL	154 A8	142 A8
15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	12	TL	157 A8	145 A8
15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	14	TL	160 A8	148 A8
15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	SPL	14	TL	160 A8	148 A8
15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	16	TL	163 A8	151 A8
16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	10	TL	158 A8	146 A8
16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	12	TL	163 A8	151 A8
16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	16	TT	168 A8	155 A8
16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	16	TL	168 A8	155 A8
400/80 - 24	W 13	W 12; W 14 L	394	1262	566	3655	IND	-	TL	-	-
400/80 - 24	W 13	W 12; W 14 L	394	1262	566	3655	IND	-	TL	-	-

STD: Standard
SPL: Special
IND: Industrial

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

2660 West Market St. Suite 100
Fairlawn (Akron) OH 44333, USA
Tel: (+1) 330 836 1090
Fax: (+1) 330 836 1091
Toll Free: (+1) 888 660 0662

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 905 641 5636
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711

bkt-tires.com

